

BOESHIELD® T-9 (AEROSOL)

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	BOESHIELD® T-9 (Aerosol)
Product Code	T90004 and T90012

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Multi-purpose Lubricant
Uses Advised Against	None

Company Identification	PMS Products Inc 76 Veterans Dr., Ste 110 Holland, MI 49423
------------------------	---

Telephone	(800) 962-1732
-----------	----------------

Emergency telephone number

EMERGENCY CONTACT: CHEMTEL (#MIS496743)
PHONE : 800-255-3924 (US / Canada)
PHONE : +01-813-248-0585 (International)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1

Label elements

Hazard Symbol



DANGER

Signal word(s)

Hazard Statement(s)

Extremely flammable aerosol
Pressurized container; may burst if heated
Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.
Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation
Wear protective gloves.
Avoid breathing spray.
Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.
IF ON SKIN: Wash with plenty of soap and water. If irritation (redness, rash, blistering) develops, get medical attention.
Keep out of reach of children.

Precautionary Statement(s)

Other hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

BOESHIELD® T-9 (AEROSOL)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Petroleum distillate	40-50	64742-47-8	Asp. Tox. 1; H304 STOT SE 3; H336 Aquatic Acute 2; H401 Aquatic Chronic 2; H411
Hydrotreated Heavy Petroleum Naphtha	20-30	64742-48-9	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Asp. Tox. 1; H304 STOT SE 3; H336
Distillates (petroleum), Hydrotreated Heavy Naphthenic	10-15	64742-52-5	Asp. Tox. 1; H304
Diethylene glycol monobutyl ether	1 - 5	112-34-5	Eye Irrit. 2A; H319
Carbon dioxide	1 - 5	124-38-9	Compressed dissolved gas; H280

Additional Information – Note: The specific chemical identity and/or percentage of composition of the remainder is being withheld as a trade secret.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation	Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.
Skin Contact	Wash affected skin with soap and water. If irritation (redness, rash, blistering) develops, get medical attention.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Do not induce vomiting. Do not give anything by mouth to an unconscious person. Get immediate medical attention.

Most important symptoms and effects, both acute and delayed May be fatal if swallowed and enters airways. Do NOT induce vomiting.

Indication of any immediate medical attention and special treatment needed IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media	Extinguish with carbon dioxide, dry chemical, foam or water spray.
-Unsuitable Extinguishing Media	Do not use water jet.

Special hazards arising from the substance or mixture

None

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

BOESHIELD® T-9 (AEROSOL)

Environmental precautions

None

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections

None

Additional Information

None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only. Do not use in confined spaces.

Conditions for safe storage, including any incompatibilities

-Storage temperature

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Keep container tightly closed.

-Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

Specific end use(s)

Lubricant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Mineral oils / Oil Mist	-----	5 mg/m3	5 mg/m3 ⁽¹⁾	-----	-----	⁽¹⁾ Inhalable
Alkanes (C9-C15)	-----	-----	1200 mg/m3	-----	-----	-----

Recommended monitoring method

NIOSH 1550 (Naphthas); NIOSH 5026 (Oil mist; mineral)

Exposure controls

Appropriate engineering controls

Ensure adequate ventilation.

Personal protection equipment

Eye/face protection

Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely (Nitrile rubber or Butyl rubber). Check with protective equipment manufacturer's data.



Respiratory protection

Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.



Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Aerosol spray

BOESHIELD® T-9 (AEROSOL)

Color.	Light amber
Odor	Petroleum solvent
Odor Threshold (ppm)	Not available
pH (Value)	Not applicable
Melting Point (°C) / Freezing Point (°C)	Not available.
Boiling point/boiling range (°C):	193°C (380°F)
Flash Point (°C)	-50°C (122°F)
Evaporation Rate	>1 (nBA = 1)
Flammability (solid, gas)	Not applicable
Explosive Limit Ranges	Not available
Vapor pressure (Pascal)	66.66
Vapor Density (Air=1)	Not available
Density (g/ml)	0.82
Solubility (Water)	Nil
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	Not available
Decomposition Temperature (°C)	Not available
Kinematic Viscosity (cSt)	Not available
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing
Other information VOC/MIR	<25 percent/<0.45

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	This product should be stored away from sources of strong heat or oxidizing chemicals.
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Acrid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Hydrotreated Light Distillate (CAS No. 64742-47-8) - By analogy with similar materials:

Acute toxicity	Oral: LD50 >5 g/kg-bw Dermal: LD50 >2 g/kg-bw Inhalation: LC50 >20 mg/l (Vapor), 4-hr. rat - May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Irritation/Corrosivity	Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Sensitization	It is not a skin sensitizer.
Repeated dose toxicity	No data
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity	Not to be expected
Reproductive toxicity	Not to be expected
Information on toxicological effects	

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

BOESHIELD® T-9 (AEROSOL)

Petroleum Distillate (64742-47-8) - By analogy with similar materials:

Short term	LC50 (96 hour): 2.5 mg/L (fish) EC50 (48 hour): 1.4 mg/L (crustacea) EC50 (72 hour): 1.3 mg/L (algae)
Long Term	NOEC (28 days): 0.098 mg/L (fish) LOEC (21 days): 1.2 mg/L (crustacea) LOEL (72 hour): 1 mg/L (algae)
Persistence and degradability	Biodegradable
Bioaccumulative potential	The product has no potential for bioaccumulation.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
-------------------------	---

SECTION 14: TRANSPORT INFORMATION

By land: DOT Proper Shipping Name: None required per 49 CFR 173.306(i) for products that conform to the Limited Quantity Provisions. Commodity shipping description: Lubricant, NOI

By water: DOT & IMDG Proper Shipping Name: UN1950, Aerosols, 2.1, LTD QTY

By air: DOT & IATA Proper Shipping Name: UN1950, Aerosols, flammable, 2.1, LTD QTY (packing instruction Y203 applies)

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
None	----	----	----

SARA 311/312 - Hazard Categories: See SECTION 2: HAZARDS IDENTIFICATION

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
None	----	----

SARA 302 - Extremely Hazardous Substances (40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None	----	----

BOESHIELD® T-9 (AEROSOL)

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 3, 9.

Date of preparation: September 3, 2026

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H222: Extremely flammable aerosol.
- H229 Pressurized container: may burst if heated.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H401: Toxic to aquatic life.
- H411: Toxic to aquatic life with long lasting effects.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.